



Mobil 1 Turbo Diesel Truck 5W40

Mobil Passenger-Vehicle-Lube , United States

Supreme Performance Heavy Duty Diesel Engine Oil

Product Description

Mobil 1™ Turbo Diesel Truck 5W-40 is a fully synthetic performance heavy duty diesel engine oil that helps to extend engine life while providing long drain capability and fuel economy for modern diesel engines operating in severe applications. Mobil 1 Turbo Diesel Truck utilizes state-of-the-art technology to help deliver exceptional performance in modern low emission engines, including refrigerated units, as well as older, well-maintained engines. Mobil 1 Turbo Diesel Truck 5W-40 is recommended for use in a wide range of light-duty applications such as turbo diesel pick-up trucks, as well as, heavy-duty applications and operating environments found in the on-road transport and off-road mining, construction, and agricultural industries. Mobil 1 Turbo Diesel Truck is suitable for use in gasoline engines used in mixed fleets.

The performance of Mobil 1 Turbo Diesel Truck 5W-40 is the result of extensive cooperative development work with major equipment builders and application of the latest lubrication technology.

Features and Benefits

Many modern, low emission diesel engines generate more soot and operate at higher temperatures than older engines. This significantly increases the need for supreme performance lubricants. Current tighter engine designs reduce oil consumption, resulting in less fresh oil makeup to replenish depleted additives. Top piston rings are located higher, bringing the oil film closer to the combustion chamber and exposing the lubricant to severe thermal stresses. Mobil 1 Turbo Diesel Truck 5W-40 helps to maintain outstanding performance at significantly higher temperatures than other high performance diesel engine oils. It is also fully compatible with conventional oils. The key potential benefits include:

| Features | Advantages and Potential Benefits |
|---|--|
| Meets or exceeds demanding specifications of major OEMs | One engine oil for mixed fleet operations |
| Outstanding thermal and oxidation stability | Helps to reduce low temperature sludge build-up and high temperature deposits |
| Enhanced film strength at high temperatures | Helps to reduce engine scuffing and bore polishing |
| Inherent stay-in-grade shear stability | Wear protection and reduced oil consumption; helps to maintain viscosity in severe, high temperature service |
| Advanced formulation and viscometrics | Aids fuel economy |
| Low volatility | Helps to control oil consumption |
| Exceptional low temperature pumpability | Easy engine start-up and helps to reduce wear |
| Enhanced TBN quality reserve | Helps to deposit control and extended drain capability |
| Outstanding resistance to corrosion | Helps to extend life of critical wear surfaces |
| Long drain capability | Helps to increase operating efficiency and lower overall cost |
| Component compatibility | Long gasket and seal life, helps to extend service intervals |

Applications

Mobil 1 Turbo Diesel Truck 5W-40 is recommended for use in all super high performance diesel applications, including modern low emission engine designs with Exhaust Gas Recirculation (EGR). These applications include the following:

- On-highway engines operating in both high speed/high load and stop-and-go conditions
- Off-highway engines operating in severe low speed/heavy load conditions
- Virtually all diesel powered equipment from American, European, and Japanese equipment builders
- High performance gasoline engines and mixed fleets
- Refrigeration units

Specifications and Approvals

This product is recommended for use in applications requiring:

API CG-4

This product meets or exceeds the requirements of:

API CJ-4

API CI-4 PLUS

API CI-4

API CH-4

API SM

API SL

Caterpillar ECF-3

API CK-4

API SN

ACEA E7

ACEA E9

Properties and Specifications

| Property | |
|--|-----------|
| Grade | SAE 5W-40 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 13.7 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 83 |
| Density, 15.6C, g/cm ³ , ASTM D4052 | 0.853 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 234 |

| Property | |
|--------------------------|-----|
| Pour Point, °C, ASTM D97 | -48 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389


1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved